

Thin skim-on floor coating

A coloured, thin film cement based floor covering which is versatile and durable. It is a two coat system which produces a 1.6mm smooth decorative finish ideal for internal domestic renovations. Comes complete with powder and catalyst as a twin pack.

BENEFITS

- Thin skim-on coating perfect for renovations
- Interior use only
- Application with a steel trowel
- Versatile application can be used to coat counters & vanities
- Reaches a compressive strength of 35MPa after 28 days (this is solely dependent on the substrate)

SPECIFICATIONS

Suitable surfaces	Wood or steel floated concrete floor slabs or screeds (interior only) New surfaces should be allowed to cure for at least 28 days Tiles - as long as the necessary preparation steps are followed to ensure adhesion. Refer to coating over tiles datasheet
Finish	Smooth
Thickness	1.6mm (maximum 0.8mm per coat – 2 coat application)
Application	Sponge 8 trowel-on
Packaging	15kg twin-pack container
Coverage	8 - 10m² per 15kg container
Curing	The completed work should be allowed to air cure for 24 hours after application, before mist spraying the entire floor evenly at least twice during the day thereafter Thereafter leave approximately 48 hours before sealing The moisture in the floor must be less than 5% prior to sealing
Colour/s	Available in 11 colours

INTENDED FOR USE WITH

Concrete Primer CreteSeal Water-Based



CRETECOTE | COLOUR RANGE



Lid you know

CreteCote is a micro coating and was created to provide the look and feel of concrete, but at a fraction of the cost and weight of real concrete.



CRETECOTE | USES





CreteCote in a custom colour coated _floors & built-in seating



